

# Reelworks - 701 Series

## SPRING REWIND HOSE REELS

The 701 Series are constructed in blue impact resistant polypropylene. Each unit comes supplied with fitted hose and integral wall/overhead pivoting mounting bracket. Both models are supplied with 15m of hose and are suitable for either compressed air or water delivery.

### FEATURES:

- Light weight and durable from just 8.6 kgs
- Constructed in high-impact UV stabilised polypropylene
- Supplied with fitted PVC hose for immediate installation
- Fully assembled, includes 3' connecting hose
- Suitable for compressed air and water
- Integral wall/overhead mounting bracket
- Latching of hose at any length
- Fully automatic hose rewind for neat and tidy storage
- Virtually maintenance free
- 12 month manufacturer's warranty

**Reelworks**  
The Reel Experts

Item	Temp. °C	Max Pressure (psi/bar)	Hose Capacity		Dimensions (cm)	NW/GW (kgs)
			I.D. (inch)	Length (ft/m)		
C701-100	60	300/20	3/8"	50'/15	40H x 22W x 44D	8.6
C701-200	60	300/20	1/2"	50'/15	40H x 22W x 44D	9.6



# Reelworks - 705 Series

## SPRING REWIND HOSE REELS

The 705 Series are constructed in blue impact resistant polypropylene. Each unit comes supplied with fitted hose and integral wall/overhead pivoting mounting bracket. Both models are supplied with either 33' x 1/4" or 25' x 5/16" hose and are suitable for either compressed air or water delivery.

### FEATURES:

- Light weight and durable just 5.7kgs
- Constructed in high-impact UV stabilised polypropylene
- Supplied with fitted PVC hose for immediate installation
- Fully assembled, includes 3' connecting hose
- Suitable for compressed air and water
- Integral wall/overhead mounting bracket
- Latching of hose at any length
- Fully automatic hose rewind for neat and tidy storage
- Virtually maintenance free
- 12 month manufacturer's warranty

For up to date information and prices please visit our web site - [www.redashe.co.uk](http://www.redashe.co.uk)

Item	Temp. °C	Max Pressure (psi/bar)	Hose Capacity		Dimensions (cm)	NW/GW (kgs)
			I.D. (inch)	Length (ft/m)		
C705-100	60	180/12	1/4"	33'/10	31H x 16W x 34D	5.7
C705-200	60	180/12	5/16"	25'/8	31H x 16W x 34D	5.7

