

SHW Spring Rewind Welding Reels

OXY-ACETYLENE / OXY-PROPANE (max 200psi)

SHW reels are designed for twin hose oxy-acetylene or oxy-propane gas applications. The robust powder coated steel construction combines maximum stability with ease of use while the dual ported swivel features multiple O rings for positive gas separation. The automatic hose rewind minimises the risk of hose damage and removes the potential trip hazard of loose hose from the floor. All SHW reels feature spark-free operation for added safety.

FEATURES:

- Heavy duty steel construction with durable blue powder finish
- Double supported solid 1" steel axle
- Multi-position roller arm gives full range of mounting options
- Four way, non-sag roller guides to reduce hose wear
- 1/4" steel mounting base for maximum stability
- Slotted and drilled mounting holes for easy installation
- Spark-free latching mechanism locks hose at any length
- Fully automatic hose rewind for neat and tidy storage
- Externally mounted dual ported swivel with multiple O rings
- All working parts fully accessible for servicing
- Supplied as bare reel - Hose extra



Model Reference	Hose Capacity			Max PSI	Swivel In/Out	Size Index
	I.D.	O.D.	Feet			
SHWL-N-140	1/4"	1/2"	40	200	1/4" BSPM	1
SHWL-N-340	3/8"	5/8"	40	200	3/8" BSPM	1
SHWL-N-375	3/8"	5/8"	75	200	3/8" BSPM	2

See price list for hose options available on these reels

Size Index	Reel Dimensions			Approx Weight Less Hose
	W	H	D	
1	9 1/4"	21"	19 5/8"	25 kg
2	9 1/4"	25 1/2"	23"	37 kg

Reelworks - 808 Welding Series

SPRING REWIND HOSE REELS

The Redashe 808 Welding Series, are a high performance spring rewind hose reel, constructed in black powder-coated steel. Reels are supplied as standard without hose, but have capacities of either 50' x 3/8" twin or 65' x 1/4" twin gas hoses. Suitable for either wall, floor or ceiling mount.

FEATURES:

- Heavy duty steel construction with a durable black powder coat finish
- Full flow, brass swivel assembly, ensures maximum product delivery
- Double 'O' ring design to prevent leakage
- Latching of hose at any length
- Positive latching action
- Four way roller guides to prevent hose wear
- Multi-position guide arm to suit most mounting positions
- Sold as a bare reel. Hose at extra cost

For up to date information and prices please visit our web site - www.redashe.co.uk

Reelworks
The Reel Experts



Item	Inlet/Outlet (inch)	Max Pressure (psi/bar)	Hose Capacity			Dimensions (cm)	NW/GW (kgs)
			I.D.	O.D.	Length (ft/m)		
C808-165W	3/8" x 3/8"	200/14	1/4"	1/2"	65/20	55H x 22W x 53D	11/13kg
C808-350W	3/8" x 3/8"	200/14	3/8"	5/8"	50/15	55H x 22W x 53D	11/13kg

