

CTWA Redashe Stainless Steel, Spring Rewind Hose Reels

COMPACT, SPRING REWIND, STAINLESS STEEL HOSE REELS

CTWA Compact, stainless steel hose reels. Constructed in a heavy gauge 304 grade stainless steel, for strength, performance and reliability. Designed for harsh, corrosive environments, or where hygiene is of primary importance. They are ideally suited to washdown applications, in food processing and chemical manufacturing, but are also ideal for offshore/marine applications. Their compact size both in height and width make this an ideal unit for both small washdown areas to large processing plants. Standard length of hose 15m x 1/2" with a maximum working pressure of 300psi.

FEATURES:

- Constructed in heavy gauge 304 grade stainless steel
- Rolled and ribbed side discs for strength and rigidity
- Large 4-way roller guide to reduce hose wear
- Externally mounted spring canister
- Floor, wall mounting options
- Compact Design
- 2-year manufacturer's warranty
- Supplied as bare reel, hose available at extra cost



Model	I.D.	O.D.	Length	Max Pressure	Swivel In/Out	Reel Dimensions (mm) W x D x H	Weight (kg)
CTWA-1315SS	1/2"	7/8"	15m	300 psi	1/2" / 1/2"	285 x 375 x 367	15

For Trigger Operated Water Guns
Turn to page 61



CCRHA-SS Stainless Steel Reel

CCRHA-SS (AIR, WATER, OIL & DIESEL)

Stainless steel, high capacity spring rewind hose reels. Constructed in heavy gauge 304 grade stainless steel, offering strength performance and reliability, along with a professional and modern look. They are ideally suited to wash down, in food processing, marine & offshore applications.

FEATURES:

- 304-grade stainless steel construction
- Rolled and ribbed side discs for strength and rigidity
- Large four-way roller guide to reduce hose wear
- Supplied as bare reel, hose at extra cost
- Swept riser assembly for easy hose installation
- Fitted with viton seals as standard
- Latching of hose at any length
- Swivels have a twin 'O' ring design for extended trouble free service
- Externally mounted, fully lubricated spring canister
- Externally mounted swivel assembly for easy maintenance
- 2-year manufacturers warranty
- Supplied as bare reel, hose available at extra cost (please specify application)



Model	I.D.	O.D.	Length	Max Pressure	Swivel In/Out	Reel Dimensions (mm) W x D x H	Weight (kg)
CORHA-1320SS	1/2"	7/8"	20m	2500 psi	1/2" F / 1/2" F	378 x 525 x 485	24
CORHA-1330SS	1/2"	7/8"	30m	2500 psi	1/2" F / 1/2" F	378 x 575 x 540	30
CORHA-1920SS	3/4"	1 1/8"	20m	1500 psi	3/4" F / 3/4" F	378 x 575 x 565	30
CORHA-1930SS	3/4"	1 1/8"	30m	1500 psi	3/4" F / 3/4" F	448 x 625 x 620	45
CORHA-2520SS	1"	1 1/2"	20m	1200 psi	1" F / 1" F	448 x 575 x 565	48



KOREEL