Pathfinder Hose Reels

PATHFINDER SPRING REWIND HOSE REELS

STANDARD FEATURES:

- Constructed in heavy gauge powder coated steel.
- Finished in a durable, white powder coated gloss finish.
- Latching of hose at any length.
- Fully automatic hose rewind for neat and tidy storage.
- Extended roller guide aperture to ease hose stacking.
- Externally mounted swivel assemblies.
- Viton seals and nylon backup rings as standard.
- Low, Medium and High pressure applications.
- Double supported 1", solid steel axle.
- Pathfinder® Self-adjusting roller guide arm.
- All working parts fully accessible for servicing.
- Floor, wall or ceiling mounting options.
- Suitable for Air, Water, Oil, Diesel and Grease delivery.







COMPACT PATHFINDER:

Model	Length	I.D.	Pressure	Colour	Mounting
PFS-CDM1	8m	6mm	200psi	White	Bench
PFS-WDM1	8m	6mm	200psi	White	Wall

FEATURES & BENEFITS OF THE CONCEPT:

- Eliminates the use of a fixed guide arm in a wall/ceiling mount position.
- Easy to install with no need for post installation adjustments.
- Unique, automatic, 90° vertical rotational
- Covers various mounting positions.
- Balanced clock spring produces enough torque to displace the weight of the guide
- Allows the guide arm to move vertically up and down in a smooth, effortless and fully automatic manner.

- The roller guide and arm/s will alway be directly facing the user.
- Giving total control on payout and retrieval
- Allows the units to be mounted at an increased height.
- Removes the possibility of harm to the operator, passing personnel or damage to machinery compared to low-level units.
- Roller guide arm returns to its rest position after use.
- Sets the reel ready for the next operator.

Model Reference	Length	I.D. Bore	Pressure	Colour	Reel Dimensions			Weight				
					W	Н	D	(Bare Reel)				
Low Pressure: (Weight & Dimension D Include Pivoting Wall Bracket)												
PFS-915L	15m	3/8"	300 psi	White	210mm	440mm	610mm	18.2 kg				
PFS-920L	20m	3/8"	300 psi	White	210mm	440mm	610mm	18.2 kg				
PFS-1315L	15m	1/2"	300 psi	White	210mm	520mm	690mm	23.8 kg				
PFS-1320L	20m	1/2"	300 psi	White	210mm	520mm	690mm	23.8 kg				
PFS-910W	10m	3/8" X 3/8"	200 psi	White	210mm	440mm	610mm	18.2 kg				
PFS-915W	15m	3/8" X 3/8"	200 psi	White	210mm	520mm	690mm	23.8 kg				
Medium Pressure: (Weight & Dimension D Include Pivoting Wall Bracket)												
PFS-915M	15m	3/8"	2250 psi	White	210mm	440mm	610mm	18.2 kg				
PFS-920M	20m	3/8"	2250 psi	White	210mm	440mm	610mm	18.2 kg				
PFS-1315M	15m	1/2"	2000 psi	White	210mm	520mm	690mm	23.8 kg				
PFS-1320M	20m	1/2"	2000 psi	White	210mm	520mm	690mm	23.8 kg				
High Pressure: (W	leight & Dimensio	n D Include Pivoti	ng Wall Bracket)									
PFS-615H	15m	1/4"	5000 psi	White	210mm	440mm	610mm	18.2 kg				
PFS-915H	15m	3/8"	4000 psi	White	210mm	440mm	610mm	18.2 kg				
			PFS-PWB: (Piv	oting Wall Bracket) Weight 2.7kgs							